
BRIDGEPORT STEEL garage doors



America's Favorite Garage Doors®



intellicore® insulation technology

Clopay Bridgeport™ Steel garage doors featuring Intellicore® insulation technology represent the ultimate smart choice for homeowners. Clopay's Intellicore® insulation is a proprietary polyurethane foam that is injected into our Bridgeport™ Steel doors, expanding to fill the entire structure. The result is a door with incredible strength and durability. Its dense insulation also produces a quieter door, and with one of the industry's leading R-values of 18.4, it provides year-round comfort and improved energy efficiency.



BRIDGEPORT STEEL garage doors

Bridgeport™ Steel garage doors combine the traditional symmetry of wood stile and rail door designs with the proven durability of Clopay's three-layer, steel construction. This provides exceptional strength and energy efficiency as well as quiet operation. The 2" or 1-3/8" thickness of Intellicore® polyurethane insulation with a thermal break makes these doors heat and cold resistant while the tongue-and-groove joint helps seal out wind, rain and snow. Available in narrow and extended recessed panel designs with multiple window options, three-layer Bridgeport™ Steel garage doors are virtually maintenance-free making the beautiful look a lasting impression.

3-LAYER CONSTRUCTION

- Tongue-and-groove section joints help seal out wind, rain and snow.
- Replaceable vinyl bottom weatherseal in a rust-resistant aluminum retainer helps seal out the elements.
- 2" and 1-3/8" Intellicore® polyurethane insulation filled doors come standard with 10-ball nylon rollers and heavy-duty 14 gauge steel hinges.
- Prepainted Standard White end stiles and interior steel backing create a clean, finished appearance.
- 2" and 1-3/8" Intellicore® polyurethane
 insulation filled doors comply with 2015 IECC
 air infiltration requirement of 0.40 cfm/ft² or
 less (IECC, Section C402.5.2).



& BD2NU & BD2EU MODELS





BD1NU & BD1EU MODELS





Calculated door section R-value is in accordance with DASMA TDS-163. Models with Ultra-Grain® finish and Black paint options are 25 gauge steel.



DETAIL




A true recessed stamp replicates the timeless look of a rail and stile built wood door.

STYLE




Narrow . Models BD1NU and BD2NU.



Extended
Models BD1EU and BD2EU.

WINDCODE® Doors are available to meet most regional wind load requirements. Consult your local dealer for specific information.



COLORS



- Exterior steel on solid colors has a natural woodgrain texture.
- Doors can be painted to match the home's exterior using a high-quality latex exterior paint.
 Do not use oil-based paint.
 - *Popular in select markets, Glacier White is a brighter white. † Additional charges apply.
 - Due to the printing process, colors may vary.

CUSTOM PAINT OPTION



Color Blast® finish offers more than 1,500 Sherwin-Williams® color options to complement your home. Clopay's durable two-part paint system has been thoroughly tested and is backed by a five-year warranty.

ULTRA-GRAIN® FINISH OPTION



Ultra-Grain® Oak Medium Finish



Ultra-Grain® Oak Dark Finish



Ultra-Grain® Oak Walnut Finish



Ultra-Grain® Oak Slate Finish

- Finished steel surface simulates a real stained door without the need of staining and the ongoing maintenance of wood.
- Oak woodgrain pattern runs horizontal along the rails and vertical along the stiles and panels for an authentic, natural look.
- Available in Medium, Dark, Walnut or Slate finishes that complement Clopay Entry Doors, shutters and other exterior stained wood products.
- Exterior steel surface on an Ultra-Grain[®] finish door has a stucco texture to create a more natural woodgrain appearance.
- Window frames, grilles and inserts are color matched to coordinate with the Ultra-Grain® finish patterns. All window options are available.

Additional charges apply.

NARROW PANEL WINDOW AND TOP SECTION OPTIONS

Doors range from 6' to 16' high and 7'8" to 20' wide. Consult your Clopay Dealer for size options. Illustrations simplified for clarity. 9'0"-10'0" HEIGHTS **MODELS** BD1NU AND BD2NU WIDTHS 7'8"-10'0' 11'6"-14'6" 14'10"-19'0' 19'2"-20'0" 7'8"-10'0" 7'8"-10'0" Extended Solid Top ARCH1 Plain Short Vertical Grille addi iliba 4411 Man 4411 Man on ARCH1 Plain Long Grille on ARCH1 -----REC12 ARCH2 ER EN HE EE REC14 Vertical Grille BREE BEEL on ARCH2 SQ22 Grille on ARCH2 481b 481b 411: 411: 411: 411: SQ24 ARCH3 Trenton® Short[†] Vertical Grille arte star char star SEE SEE SEE SEE SEE SEE SEE ALLE DELL DELL DELL on ARCH3 Trenton® Long[†] Grille on ARCH3 --------- LDUE 1911 LDL Kristin® Short† Clayton™ Short† Kristin® Long† Clayton™ Long[†] 480 Wrought Iron Short*† Wrought Iron Arch*† 5,000 0 5,000 0 5 2006 0 5 2006 0 5 2006 0 5 2006 0 Wrought Iron Long*† HER KER KER KER

*Acrylic

[†]Complements Clopay Entry Door glass.

Note: Due to stile width restrictions, some odd size door widths may allow only for the installation of a single handle. See your Clopay Dealer for details.

EXTENDED PANEL WINDOW AND TOP SECTION OPTIONS



Windows in Detail







ARCH1



Vertical Grille on ARCH1



Grille on ARCH1



Grille on ARCH2









SQ24

REC12

第2篇





Trenton® Short









Kristin® Lona

000000 Clayton™ Long*







Wrought Iron Long*



Wrought Iron Arch


Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit www.clopaydoor.com/acrylic for complete details.

*Complements Clopay Entry Door glass. Long and short windows may be used in any Bridgeport 3-layer model. Double-strength glass is standard. Optional obscure, 3/4" insulated and 3/4" insulated obscure glass is available on all Bridgeport 3-layer models. Additional charges for optional glass apply.

Windows are available single pane or insulated in clear, frosted, seeded, obscure and rain designs. Clear acrylic also available



Clear









Seeded



Obscure



Additional Features



Large authentic arch window designs. Window frames, grilles and inserts are color matched to coordinate with the Ultra-Grain® finish patterns.



All Intellicore® polyurethane insulated doors come standard with 10-ball nylon rollers and heavy-duty 14 gauge steel hinges.



Hot-dipped galvanized steel interior and exterior skins with a baked-on primer and top coat help ensure a virtually maintenance-free door with long-lasting beauty.

- See your Clopay Dealer for WINDCODE® door availability.
- For more information please visit www.clopaydoor.com or try a design on your home by visiting: www.clopaydoor.com/door-imagination-system

Environmental Assurance

Clopay doors are compliant with environmental laws and regulations. Clopay doors do not contain HFCs. All Clopay doors are compliant with:

- California SB 1013
- New Jersey A-5583/S-3919 Greenhouse Gas Bill
- Washington HB 1112 Hydrofluorocarbon Greenhouse Gas Emissions
- Canadian regulations amending the ozone-depleting substances and halocarbon alternatives regulations

Decorative Hardware





Doors come standard with color-matched lift handles.

OPTIONAL



Note: Decorative hardware options vary based on door widths. Standard hardware is not provided if a lock is chosen. Some odd size door widths may allow only for the installation of a single handle. See your Clopay Dealer for details.











[†] Aluminum construction.

Door may not open properly if installed near the top depending on opening dimensions and lift type. See your Clopay Dealer for more details.

Warranties



LIMITED **10 YR** WARRANTY

LIMITED 3YR WARRANTY



Visit clopaydoor.com or call 1-800-2CLOPAY (225-6729) for more information on Clopay, America's Favorite Garage Doors.

Follow us on















@ 2021 Clopay Corporation. All rights reserved.

RSDR-BRIDGEPORT3LAYERSS-20_REV0421

imagine



DESIGN YOUR DOOR OPEN CAMERA AND POINT!